

Criosu – Probe Sensor CC767-P-C-Whi-C-SV



Technical Specification

Model: CC767-P-C-Whi-C-SV

CC767-T-M-F-S-SV

T-Type

C -Connector

T-Timple

P-Plate

M - Material

A - ABS Plastic

S - Steel

C - Ceramic

F - Finish

Whi - White

Bla - Black

BSS - Brushed Stainless Steel

MCR - Mirrored Chrome

S - Shape

F - Flat

C - Curved

SV - Screws Visibility

SV - Screws Visible

SNV - Screws Not Visible

User Interface

Via Central Console

Temperature

Ch 1	Air
------	-----

Type

Function	Temperature Measurement
Internal Probe	Probe (NTC10K)

Mechanical

Dimensions (Fitted)	9mm X 88mm x 88mm (D x L x H) (Installed)
Material	Ceramic
Mounting	Wall Mounted – 2 fixed Points
Protection Rating	IP50 (when mounted)
Finish	White

Environment

EMC Immunity	EN61000-6-1
EMC Emissions	EN61000-6-3
Ambient Temperature	0-40°C
Ambient Humidity	0-90% RH non -condensing

Electrical Wiring

Terminations

Connection Points	2 Way Screw Terminal
Cable	2 Core 24 awg (7/32awg - 0.2mm) stranded tinned annealed copper conductors 100% Overall foil screened Colour Coded UL2464 compliant

Features

Feature List

Applications	Heating & Cooling
Zone Thermostat	SP - Set Point : SB - Set Back : BH - Boost heat
7 day Programmable Timer	24 Hr, 20 Min Segments, Individual Timer for each Zone
Optimization	4 Settings including an automatic learning mode
Stop- Set Back Mode	Ignores timer schedule, moves to Set Back
Frost Protection Mode - Disable	Ensure all plumbing is protected against frost
Accuracy	Accuracy of 1.0C
Central Control at the console	Console
Set Back Tracking	Ensure the Set Back always follows the Set Point

Please note:

Criosu Controls employs continuous development which sometimes necessitates specification changes without notice. Please contact Criosu Controls for latest revision.