

ILLELI

mmm m

Man Par

1111

11.1

11

ININ

A.



iCon® system

The iCon® system is a centrally controlled advanced energy management system that integrates multiple energy sources such as boilers, geothermal pumps, Fan Coil Units, VRFs and solar panels. It's configurable architecture enables designers to readily build systems for the most demanding project requirements.







cc764 Series BSS

cc764 Series

BLK

cc764 Series WHI






BSS









Meeting Client Requirements for over 15 years

Energy Efficient Zone Control

32 Zones
Multiple SP & Time Slot Scheduling
Multiple Season Scheduling
Programmable Boost Heat
Advanced Mode Control
Built-in Legionella Control
Boost Heat in Cost efficient Tariff Periods
Stop & Disable Zone Control
Heat Source Prioritization
Weather Compensation
Auto Optimization
Historical Log
Cenari Jacov HU Apartment Layout More
Simple Operation at Sensor

sor

Simple 3 Button Sensor Operation Single Touch Temperature Control Single Touch Mode Control Sensor Lockout Individual Zone Labelling

Integrated Heating & Cooling Integration of 3rd Party Devices

Configuration

Wood Floor Protection

Wood Floor Protection Initial Heat-up Sequence **Relative Humidity** Dew Point (Bs En 1264 4 2001).

Neworking

Modbus Master (RS485) Modbus Slave (RS485) REST api (Ethernet)

Alarms SMS & Email

App - Remote Control

Complete control of system Multiple Device platforms (android, ios..) Attended and Unattended Access encryption 128-bit AES

App - Central Management

Distributed Control Nursing Homes, Schools, Hotels...

App - **Project Management**

Desktop Creation of Project **Engineering Drawings** Cloud Storage of Project Project Update (local and remote) App update (local and remote)





Integration

Management Systems Environment Control **Ancillary Systems** Tempertature BMS Home Automation Temperature **Relative Humidity** Dew Point Dial Stat Lights Pool **Digital Sensor** Plate Sensor

Heating & Cooling Exananges





Exchanger


Ventilation

Heat Pump





Configuration








Seamless Heating and Cooling



Single Point Contol

Heating and Cooling is fully and seamlessly integrated into a single control point at the sensor. Control involves the press of the up and down buttons






Boiler





Protection of Wooden Floors



Initial Heat-Up Sequence

The Initial Heat-up sequence is carried out over 21 days after the laying of cement screed or, in accordance with the manufacturer's instructions but at least 7 days in the case of anhydrite screeds.

(Bs En 1264 4 2001).

Continuous Monitoring

Screed probes protect wooden finishes by continuously monitoring the screed

Relative Humidity & Dew Point


Big increases in humidity can affect wood floors badly. Depending on the floor type, manufacturers recommend humidity be kept between 40-70%RH



iCon[®] Intelligent Control




Prioritized Heating

















VRF



iCon[®] Intelligent Control



App - Remote Access







App - Central Management







App - Project Management

